

5-1000MHz 防水过流型分支分配器

MW-□7□E



技术指标

分支器 (17□-□□E)

项 目		单位	性能参数																							
			一分支器（171 - □□E）								二分支器（172 - □□E）								三/四分支器（173/4 - □□E）							
分支损耗	标称值		8	10	12	14	16	18	20	8	10	12	14	16	18	20	10	12	14	16	18	20	22			
	允许偏差	dB	±1.5								±1.5								±1.5							
插入损耗 （≤）	5-65MHz	dB	2.5	2.0	2.0	1.9	1.5	1.0	1.0	4.0	3.3	2.5	2.3	2.0	2.0	1.5	4.3	4.3	2.0	1.7	1.5	1.0	1.0			
	65-550MHz		2.5	2.0	2.0	1.7	1.0	1.0	1.0	4.0	3.3	2.5	2.3	2.0	2.0	1.5	4.3	4.3	2.5	2.5	1.5	1.2	1.2			
	550-750MHz		2.5	2.5	2.0	2.1	1.5	1.5	1.5	4.0	3.7	2.9	2.5	2.0	2.0	1.5	4.5	4.5	2.5	2.5	1.7	1.5	1.5			
	750-1000MHz		3.0	2.7	2.5	2.2	1.5	1.5	1.5	4.0	3.7	2.9	2.5	2.0	2.0	1.5	4.5	4.5	3.5	3.5	1.7	1.7	1.7			
反向隔离 （≥）	5-65MHz	dB	18	20	22	22	24	26	26	22	22	22	26	26	26	30	22	25	30	30	30	30	30			
	65-550MHz		20	22	25	25	27	28	30	25	22	25	26	26	26	30	25	25	28	28	28	28	30			
	550-750MHz		20	20	22	22	22	22	22	20	20	20	22	22	26	28	22	22	22	22	25	25	25			
	750-1000MHz		20	20	22	22	22	22	22	18	20	20	22	22	24	24	22	22	22	22	22	25	25			
相互隔离 （≥）	5-65MHz	dB									22								25							
	65-550MHz										30								25							
	550-750MHz										22								23							
	750-1000MHz										20								20							
反射损耗 （≥）	5-65MHz	dB	14								14								14							
	65-550MHz		16								16								16							
	550-750MHz		14								14								14							
	750-1000MHz		14								14								14							
屏蔽衰减		dB	≥ 100								≥ 100								≥ 100							
信号交流声比		dB	≥66								≥ 66								≥ 66							
通过电压		V	~ 60(50Hz)								~ 60(50Hz)								~ 60(50Hz)							
端口载流能力		A	6~10								6~10								6~10							

分配器 (77□E)

项 目		772E	773E	774E	项 目	772E	773E	774E	项 目	772E	773E	774E	项 目	772E	773E	774E
分配损耗 (dB)	5-65MHz	4.5	7.5	8.0	反射损耗 (dB)	14			信号交流声比 (dB)	≥66			端口载流能力 (A)	6~10		
	65-550MHz	4.5	6.8	8.0		16										
	550-750MHz	4.5	7.5	8.5		14										
	750-1000MHz	5.5	8.0	9.0		14										
相互隔离 (dB)	5-65MHz	22			屏蔽衰减 (dB)	≥100			通过电压 (V)	~60(50Hz)						
	65-550MHz	25														
	550-750MHz	22														
	750-1000MHz	20														