



5-1000MHz(小型)室内型分支分配器

MW-□7□H/H(S)

技术指标

项 目		单位	性能参数																							
			一分支器（171 - □□HS）								二分支器（172 - □□HS）								三分支器（173 - □□HS）							
分支损耗	标称值		8	10	12	14	16	18	20	24	8	10	12	14	16	18	20	10	12	14	16	18	20	22	24	
	允许偏差		±1.5								±1.5								±1.5							
			±1.5								±1.5								±2.0							
			±1.5								±1.5								±3.0							
插入损耗 （≤）	5-65MHz	dB	2.5	2.2	2.0	2.0	1.7	1.5	1.2	1.0	4.0	3.7	2.5	2.3	2.0	2.0	1.7	4.0	4.0	3.5	2.5	2.3	2.0	2.0	1.5	
	65-550MHz		2.0	1.8	1.5	1.5	1.2	1.0	0.7	0.5	4.0	3.3	2.5	2.3	2.0	1.5	1.2	4.0	4.0	3.5	2.5	2.3	2.0	2.0	1.0	
	550-750 MHz		2.2	2.0	1.8	2.0	1.5	1.5	1.2	1.0	4.5	3.7	2.8	2.7	2.5	2.0	2.0	4.5	4.5	4.0	2.8	2.5	2.5	2.0	1.8	
	750-1000MHz		2.5	2.2	2.0	2.0	1.8	1.8	1.8	1.8	4.5	3.7	2.9	2.7	2.5	2.5	2.0	4.5	4.5	4.0	3.0	3.0	3.0	2.8	2.8	
反向隔离 （≥）	5-65MHz	dB	20	22	22	24	26	28	30	30	18	20	22	24	26	28	30	30	20	22	24	24	30	30	30	
	65-550MHz		22	22	22	24	26	28	30	30	18	20	22	24	26	28	30	30	20	22	24	24	30	30	30	
	550-750 MHz		22	22	22	22	26	28	30	30	18	20	22	22	26	25	28	28	20	22	22	22	25	28	28	
	750-1000MHz		20	20	20	22	24	24	26	26	13	15	17	19	21	23	25	28	18	18	19	21	23	25	25	
相互隔离 （≥）	5-65MHz	dB									22								22							
	65-550MHz										25								25							
	550-750 MHz z										18								20							
	750-1000MHz										18								18							
反射损耗 （≥）	5-65MHz	dB	14								12								12							
	65-550MHz		16								16								16							
	550-750MHz		14								12								12							
	750-1000MHz		14								10								10							
屏蔽衰减		dB	≥100								≥100								≥100							

项 目			单位	性能参数								项 目		单 位	性能参数			
				四分支器（174 - □□HS）											四分支器（174 - □□HS）			
分支损耗	标称值			10	12	14	16	18	20	24	相互隔离 （≥）	5-65MHz	dB	22				
	允许偏差	5-550MHz	dB	±1.5								65-550MHz		25				
		550-750MHz	dB	±2.0								550-750 MHz z		20				
		750-1000MHz	dB	±3.0								750-1000MHz		18				
插入损耗 （≤）	5-65MHz		dB	4.0	4.0	3.5	2.5	2.3	2.0	2.5	反射损耗 （≥）	5-65MHz	dB	12				
	65-550MHz			4.0	4.0	3.5	2.5	2.3	2.0	2.5		65-550MHz		16				
	550-750 MHz			4.5	4.5	4.0	2.8	2.5	2.5	2.8		550-750 MHz z		10				
	750-1000MHz			4.5	4.5	4.0	3.0	3.0	3.0	3.0		750-1000MHz		10				
反向隔离 （≥）	5-65MHz		dB	20	22	24	24	30	30	30	屏蔽衰减		dB	≥100				
	65-550MHz			20	22	24	24	30	30	30								
	550-750 MHz			20	22	22	22	25	28	28								
	750-1000MHz			18	18	19	21	23	25	25								